

FriendlyELEC Zero2 Combo with Case 1GB

>>> [Zum Shop-Artikel](#)



EAN CODE



FriendlyELEC Zero2 Combo with Case 1GB

- SoC: Rockchip RK3528A
 - CPU: Quad-core ARM Cortex-A53
 - GPU: ARM Mali-450 GPU
 - VPU: 4K H265/H264 60fps decoding
- RAM: 1GB/2GB LPDDR4/LPDDR4X
- Flash: Supports eMMC Module
- Ethernet: one Native Gigabit Ethernet
- M.2 Key-E 2230 connector with PCIe 2.1
- USB Ports:
 - One USB 2.0 Host Type-A port
 - One USB 2.0 Device Type-C port for eMMC upgrade
- One microSD Slot
- One 30-pin FPC GPIO connector
- Debug: Debug UART, 3.3V level, 1500000bps
- LEDs: 2 x GPIO Controlled LEDs (SYS & LED1)
- others:
 - 2 Pin 1.27/1.25mm battery connector for Low-power RTC
 - RESET Button, RECOVERY Button, and MASK Button for eMMC upgrade
- Power supply: DC 5V/2A, via USB-C connector or 2.54mm Header
- PCB Size: 45*45*1.2mm
- Temperature measuring range: 0? to 80?

https://wiki.friendlyelec.com/wiki/index.php/NanoPi_Zero2