


J1	J2	J3
1	1	1 white orange
2	2	2 orange
3	3	3 white green
4	4	4 blue
5	5	5 white blue
6	6	6 green
7	7	7 white brown
8	8	8 brown
9	9	9

PIN OUT



MATERIAL LIST:

⑧	Bottom Panel:	Fireproof PC/ABS UL-94V0(metallized)	1	
⑦	Upper Panel Cover:	Fireproof PC/ABS UL-94V0(metallized)	1	
⑥	RJ-45 JackShield:	0.25mm thickness Brass with Ni plated	2	
⑤	RJ-45 Jack:	Housing-PBT/FRP 8P8C 3u" gold plated	2	
④	PCB:	FR-4/1.6mm UL-94V0	1	
③	Cable:	STP Cable(ivory)	1	
②	Cable boot:	PVC uL-94V0(ivory)	2	
①	Connector:	RJ45 8P8C PLUG GOLD PLATED 3u"	1	
NO.			QT'Y	REMARK

NOTES:

- Electrical Specifications:
- Insulation Resistance: 500M ohms (min.)
- Contact Resistance: 20M ohms (max.)
- Current Rating : 1.5 Amps.
- DC Resistance: 0.1 ohms (max.)
- Withstanding Voltage : 1000 VAC RMS @ 60Hz/ 1 min.
- Mechanical Specifications:
- RJ-45 Jack Insertion Cycle : Over 200 Cycles (min.)
- ROHS2.0 AND REACH COMPLIANT
- PACKING:SYNERGY 21 PE BAG+LABEL

SYNERGY 21

CUSTOMER		ITEM NO.		S215234	
PRODUCT NAME	Adapter RJ45 to 2000T 8P8C	manufacturer country:	CHINA	UNIT	MM
BY	CHK	NEW	REVISION RECORD MODIFICATIONS	DATE	2014-02-10
				REV.	SYNERGY 21
					SYNERGY 21
					SYNERGY 21
					2014-02-10