

ALLNET Outdoor PoE Injector IP67 IEEE802.3bt (15.4W/30W/60W) Metal Housing / ALL-PI2013Ov2BT60

>>> Vers l'article de la boutique en ligne

DE: AC Stromkabel nur symbolisch abgebildet. Endgerät hat 2
PIN AC Klemmblock.
EN: AC power cable only shown symbolically. Terminal
device has 2 PIN AC terminal block connectors for power



EAN CODE



Highlights:

- 60 Watt PoE IP67 outdoor injector according to IEEE802.3bt standard
- IP67 weatherproof & IK10 shockproof for robust outdoor installations
- **1x 10/100/1000/2500Base-TX PoE output according to IEEE802.3af/at/bt 60W**
- 1x AC 100~240V input voltage on 2PIN terminal (AC connection cable must be installed by the customer, thus flexible in installation)
- Extended operating temperature: -20°C to +60°C


This product is an outdoor Gigabit Power-over-Ethernet (PoE) device for powering most common IP end devices. The injector is fully compliant with the IEEE 802.3af/at/bt standard. The device also fulfils the IP67 protection class, making it weatherproof and easy to use outdoors. The injector is shock-resistant thanks to the IK10 standard, which ensures reliable and safe use, even in industrial environments.

Compared to the previous version (v1), the ALL-PI2013Ov2BT60 now has a 2.5GBase-T connection and therefore enables a significantly higher data transfer rate.

It transmits the required electrical energy and realises the data exchange via an RJ45 cable with a maximum transmission distance of 100 metres. The injector automatically recognises which PoE standard is present at the end device on the output side and regulates the voltage accordingly. The injector can supply a PoE end device at the output with a maximum power of 60W in accordance with the IEEE 802.3bt standard.


Front Panel

The front panel composed by PSE output ports with data link port, AC Input port, the relevant indicator, as shown below:




Left Panel

Schematic diagram of left panel: input port (AC In) and grounding column, Standard network Cat5 cable (line diameter 5.5mm).




Right Panel

Schematic diagram of right panel: the output port (PoE out、Data) requires the use of standard network cate5 cable (Line diameter 5.5mm).



Desktop Installation

Install the machine on a desktop, place the machine carefully on the counter, the bottom is as follows:



Technical details:

Technical details:

Model:	ALL-PI2013OBT60 - 60W waterproof PoE injector AC to BT 60W
IEEE standard:	IEEE 802.3 10Base-T Ethernet IEEE 802.3u 100Base-TX Fast Ethernet IEEE 802.3ab 1000Base-T Gigabit Ethernet IEEE802.3af for POE IEEE802.3at for POE+ IEEE802.3bt



No. d'article: 257252
Numéro de fabricant: ALL-PI2013Ov2BT60

Network Media (Cable):	10BASE-T: UTP category 3,4,5 cable (=100m) 100BASE-TX: UTP category 5 cable (=100m) 1000BASE-T: UTP category 5e cable (=100m) 2500BASE-T: FTP category 6/6a cable (=100m)
Network Connector:	1xRJ-45 10/100/1000BaseT(X) Data 1xRJ-45 10/100/1000/2500BaseT(X) PSE with POE Output power IEEE802.3bt 60W
Input current:	1.5A Max
Power input:	AC 100-240V 50/60Hz 2 PIN terminal
PoE Power output:	60W Max. IEEE802.3bt
POE Pin Assignment RJ45:	1/2(-), 3/6(+)
Output Voltage:	DC 55V±5%
Output ripple voltage:	=200mV, Test conditions: rated input voltage, full load output, Tested with 20MHz bandwidth oscilloscope, Parallel connected a 0.1uF ceramic capacitor and a 10uF electrolytic capacitor to the output
Output current:	1.1A Max
LED Indicator:	PWR(Green) , PoE(Bt:Green,UPoE:orange)
Dimming:	150 x 73 x 44mm
Operating Temperature:	-20°C ~ 60°C
Storage Temperature:	-40°C ~ 80°C
Surge Protection:	Difference Mode:±4KV, Common mode:±6KV
MTBF:	<50000 hours
Electrostatic standard:	Contact 6KV, air 8KV
Waterproof grade:	IP67
impact protection rating	IK10

Attributs

Attribut	Valeur
Einsatzbereich Display:	Industrie
Gehäuse:	Metall
Geschwindigkeit Injektor:	10M (100Mbit); 100M (100Mbit); 1G (1000Mbit);
PoE Leistung:	15;30;60;
PoE Standard:	IEEE802.3af;IEEE802.3at;IEEE802.3bt;
Poids:	1 Kg



No. d'article: 257252
Numéro de fabricant: ALL-PI2013Ov2BT60

Attribut	Valeur
Garantie:	24.00 Mois