# ALLNET Replacement Power Supply QC USB-C PD GaN Power Supply 33 Watt 1x USB Type-A QC, 1x USB Type-C**EU PLUG**

>>> Go to the shop article

EAN CODE

4 0 3 8 8 1 6 1 2 5 5 5 2

ALLNET Replacement Power Supply GaN QC USB-C PD Power Supply 33 Watt **EU PLUG** 1x USB Type-A, 1x USB Type-C
Highlights:

GaN stands for the material gallium nitride, which is increasingly used for semiconductors in chargers. The advantage of GaN to silicon chargers is that it generates less heat. Less heat means that components can be placed closer together without sacrificing power capacity and in accordance with safety standards. The charging process is accelerated because the electric current can pass through the GaN components more quickly.

The QC designation stands for QuickCharge® from Qualcomm® which the power supply supports. PD is an intelligent management technology, which enables the so-called PD chips in active power cables and devices to always transmit the permitted voltage and current. It contributes extremely to safety and devices & cables can no longer be overloaded and hot.

- Input : 100V-240V ~50/60Hz 0.8A max
- PD 3.0 Output : 5V3A, 9V3A, 12V2.5A, 15V2A, 20V1.5A
- PPS Output 3.3V-11V=3A or 3.3V-16V=2A
- QC 3.0 Output : 3.6-6.5V=3A or 6.5V-9V=2A or 9-12V=1.5A
- PD+QC (5V3A)
- Total Output: 33W max.
- CE, RoHS, FCC

Very high quality power supply with PD USB-C for all modern devices with HighSpeed Charging, e.g. Quad SATA Kit for Raspberry Pi 4, Rock Pi, smartphones, tablets, netbooks and notebooks or any other devices that can be charged via USB Type-C or PD.

www.allnet.de

ALLNET GmbH - Maistraße 2 - 82110 Germering - sales@allnet.de - 089 / 894 222 22
Errors and technical changes that serve the interests of progress or development of the product, are reserved.
Page 1/2

Dimension power supply: W: 30 x H: 30 x D: 40mm (without Euro plug)

Tip:

Please use a high quality USB-C cable, this is crucial that the correct power can be transferred.

Accessories

Part No.	Name
160024	Synergy 21 USB cable USB-A to USB-C USB3.0 white
187728	Kabel USB, C(St) => A(St), 1,5m, USB3.1, Strom-/Daten Kabel zu USB 3.0 TypA
215607	Kabel USB, C(St) => C(St), 5,0m, USB3.1, black, 10G/5A, Gen 2, E-Marker Chip, aktives PD USB-C
232390	Kabel USB, C(St) => C(St), 1,5m, USB4.0, schwarz(Textil), 40G/5A, 240W, Gen 3x2, E-Marker Chip, Synergy 21,
232391	Kabel USB, C(St) => C(St), 2,0m, USB4.0, schwarz(Textil), 40G/5A, 240W, Gen 3x2, E-Marker Chip, Synergy 21,
232368	Kabel USB, C(St) => C(St), 3,0m, USB3.2, schwarz(Textil), 20G/5A, 240W, Gen 2x2, E-Marker Chip, Synergy 21
157633	Kabel USB, C(St) => A(St), 1,0m, USB3.1, schwarz, 10G/3A, Gen 2, Synergy 21,

www.allnet.de

ALLNET GmbH - Maistraße 2 - 82110 Germering - sales@allnet.de - 089 / 894 222 22
Errors and technical changes that serve the interests of progress or development of the product, are reserved.
Page 2/2