

AXIS TU9004 Wireless Dongle

Wireless USB dongle for AXIS M1075-L Box Camera

AXIS TU9004 Wireless Dongle allows the camera to communicate with 2.4 GHz and 5 GHz frequency. The wireless adapter supports 802.11ac/b/g/n. A PoE injector is required to power the camera.

- > 2.4 GHz and 5 GHz
- > Supports 802.11 α c/b/g/n/ α





www.cxis.com T10199443/EN/M1.4/2311

AXIS TU9004 Wireless Dongle

Argentina: ENACOM Australia / New Zealand: RCM

Bahamas: URCA Bahrain: TRA Brazil: Anatel Canada: IC Costa Rica: SUTEL Curaco: BURTEL

Dominican Republic: INDOTEL

El Salvador: SIGET Europe: CE Fiji: TAF Guatemala: SIT Honduras: CONATEL India: WPC Japan: TELEC Malaysia: SIRIM Morocco: ANRT Qatar: CRA Panama: ASEP Pakistan: PTA Paraguay: CONATEL Peru: MTC Saudi Arabia: CITC Sint Maarten South Africa: ICASA South Korea: KC Taiwan: NCC Thailand: NBTC Turkey: BTK UAE: TRDA United States: FCC

General Operating 0 °C to 35 °C (32 °F to 95 °F) conditions Storage -20 °C to 75 °C (-4 °F to 167 °F) conditions Dimensions 29.5 x 15 x 8 mm (1.2 x 0.6 x 0.3 in) Weight 3.3 q ± 0.25 q (0.007 lb ± 0.0006 lb) Box content Wireless adapter Warranty 3-year warranty, see axis.com/warranty **Export control** This product is subject to export control regulations, and you should always comply with all applicable national and international export or re-export control regulations. Sustainability Substance PVC free, BFR/CFR free in accordance with JEDEC/ECA Standard control RoHS in accordance with EU RoHS Directive 2011/65/EU/ and EN 63000:2018 REACH in accordance with (EC) No 1907/2006. For SCIP UUID, see axis.com/partner. Materials To read more about sustainability at Axis, go to axis.com/about-axis/sustainability Environmental axis.com/environmental-responsibility responsibility Axis Communications is a signatory of the UN Global Compact,

read more at unglobalcompact.org

