

## **DisplayPort Cable**

2M (6.6ft) / 3M (9.8ft) - rev.1.4

The ATEN DisplayPort rev.1.4 Cable supports 32.4 Gbps data rate with high-definition connectivity and advanced auxiliary channeling. It is a professional connection of your DisplayPort supported (gaming) PC, use in conjunction with ATEN DisplayPort solutions, laptop to an ultra high resolution monitor, or other DisplayPort interface devices. Our DisplayPort rev.1.4 Cable allows for up to 8K Dynamic HDR with 32 channels for high quality video and audio experience. Each connector features latches that provide a secure connection with a release button.





## Features

- Crystal-clear video up to 8K (7680 x 4320 @ 60Hz), backward compatible with 5K (5120 x 2880 @ 60Hz) and 4K (4096 x 2160 @ 120Hz) and previous generations of DP
- High Bit Rate 3 (HBR3) bandwidth of 32.4 Gbps
- Multi-Stream Transport (MST) for daisy-chaining multiple monitors
- Forward Error Correction
- Display Stream Compression (DSC)
- 32 uncompressed digital audio channels
- RoHS compliant

## **Specifications**

Function	2L-7D02DP	2L-7D03DP-1
Video Resolution	Up to 8K (7680 x 4320 @ 60Hz)	
Physical Properties		
Cable Length	2 m	3 m
Cable Color	Black	
Cable Outer Dimension	6.5 + - 0.2 mm	8.0 + - 0.2 mm
Conductor Gauge	30AWG	26AWG
Conductor Material	Tinned Copper	
Connector Plating	Nickel	
Connector Type	DisplayPort (20 pin) Male to Male	
Cable Shield Type	Aluminum Magnesium Alloy	
Cable Jacket Type	PVC	
Environmental		
Operating Temperature	80° C	
Rating	UL VW-1 (Flame rate), CSA	

## **Model List**

2L-7D02DP	2 m DisplayPort rev.1.4 Cable	
2L-7D03DP-1	3 m DisplayPort rev.1.4 Cable	



