



SPA-M1000

IP Microphone



Key Features

- Output Level: +10dBV \pm 3dB
- Frequency Response: 100Hz ~ 18kHz
- Supported Protocol: IPv4, HTTP, SIP, mDNS, DNS, NTP, TCP, UDP, DHCP, ARP, ICMP
- Power: PoE (IEEE 802.3 af type 1 Class 3), Max.10W, DC24V
- Ethernet: 100/1000 Base-T

SPA-M1000

IP Microphone



Specifications

Product	
Type	IP Microphone
Network	
Ethernet	10/100 Base-T
General	
Operating Temperature	-10 ~ +40°C (+14°F ~ +104°F)
Operating Humidity	10~85% RH (Non-Condensing)
Weight	1.29Kg
Size	200(W) x 73(H) x 206(D)mm
Color	Black & Gray
Certificate	EMC : KS C 9832/9835, EN 55032/55035, FCC Part 15 Subpart B, ICES-003 Safety : UL 62368-1, CAN/CSA 62368-1
Power	
PoE	PoE (IEEE 802.3 af type 1 Class 3), Max.10W, DC24V
Embedded MIC	
Input Sensitivity	-50dBV ± 3dB
Frequency Response	100Hz ~ 18kHz
Network Protocol	
Supported Protocols	IPv4, HTTP, SIP, mDNS, DNS, NTP, TCP, UDP, DHCP, ARP, ICMP
System Integration	
API (Application Programming Interface)	SUNAPI
Functional Monitoring	Connection verification, Built-in system logging