

ALLNET Point-to-Point Modem g.fast via 2-Wire Managed Master



EAN CODE



ALLNET point-to-point modem g.fast via 2-wire managed master "ALL-BM310"

Highlight:

- G.Fast bridge master modem
- Network via 2 wires in combination with ALL-BM300 Slave Modem (Modem is still needed extra - Please see our Bundle ALL-BM320" here)

The ALLNET ALL-BM310 is a G.fast master modem, which in combination with an ALL-BM300 can give you fast and easy access network/Internet over 2-wire cable. The modem is simply connected to a broadband router, firewall PC or MAC, no further settings are required (For VLAN settings, a VLAN ID can be configured in the web interface). Only your router/firewall/PC etc. needs to be connected to the LAN port/connector.

Technical Details:

Features:	<ul style="list-style-type: none"> • Compliant with IEEE 802.3 / 802.3u / 802.3ab Ethernet Standard • Compliant with ITU-T G.9700/G.9701 G.fast standard • Support 212a G.fast band profile • Support High Bandwidth up to 1Gbps • Support USB 3.0 for connecting USB Dongle • Support HTTP/HTTPS web management
-----------	--



	<ul style="list-style-type: none">• Support remote management and monitor• Support configuration backup and restore• On board surge protection for Line port• Support bridge(switch) ALL-BM310 Master only)• Support RJ-11 / Terminal block combo line port• Support NTP Time Server.• Support TR-069.• On board POTS/ISDN splitter• Support Jumbo frame(MTU) up to 1600 bytes
Specifications	
Standards	<ul style="list-style-type: none">• IEEE802.3/802.3u/802.3ab standards• ITU-T G9700/G9701 standards• Physical Interface
	<ul style="list-style-type: none">• 4 x RJ-45 10/100/1000 Mbps Ethernet port• 1 x RJ-11 / Terminal block combo for line port• 1 x RJ-11 connector for POTS/ISDN phone device• 1 x Reset Button for resetting to factory default• 2 x USB3.0 for connecting USB dongle
Button	<ul style="list-style-type: none">• 1 x Power LED• 4 x Link/Active Status for Ethernet port• 1 x Link LED for G.fast mode• 1 x Link LED for xDSL mode
Input Power	DC 12V / 2A including
Dimensions:	196mm x 146mm x 40 mm (7.72" x 5.75" x 1.57")
Net weight:	approx. 0.4 kg
Temperature	0°~50° C (Operating), -20° ~70° C (Storage)
Humidity	10 - 90% non-condensing
Marks	<ul style="list-style-type: none">• CE• FCC• RoHS Compliant
Package Contents:	<ul style="list-style-type: none">• 1x ALL-BM310• 1x 12V/2A Powersupply• 1x Patchcable• 1x QIG

Additional Images



Accessories

Part No.	Name
174279	ALLNET ISP Bridge Modem g.fast / VDSL2 Profile 35b/17A
128088	ALLNET Ersatznetzteil 12V/2,5A mit KEFA (Phoenix® kompatibel) (z.B. BM300/BM310)