

AXIS Camera Station S1224 Rack Recording Server

Flexible and scalable recording server

Out-of-the-box recording server, designed to provide top-class performance and reliability in a compact server product. AXIS Camera Station S1224 Rack Recording Server comes with 24 AXIS Camera Station Pro Licenses included. It comes with an extensive support, a 5-year warranty and an empty hard drive bay for storage expansion. With its powerful components and secure design, this recording server is ideal for demanding applications. Its scalability and flexibility make it easy to expand your system as needed. The product's power settings have been optimized to minimize energy consumption and maintain a controlled Total Cost of Ownership.

- > **Scalable and powerful solution**
- > **One empty hard drive bay for storage expansion**
- > **Optimized energy consumption**
- > **24 AXIS Camera Station Pro licenses included**
- > **Extensive support and 5-year warranty**



AXIS Camera Station S1224 Rack Recording Server

Licenses

24 AXIS Camera Station Pro Core Device NVR licenses included and tied to the hardware. Can be upgraded with additional licenses (sold separately).

System scalability

Qualified for 64 doors and 32 video channels with a total recording bitrate up to 300 Mbit/s. Check AXIS Site Designer for storage estimates. Can be scaled with more devices when using AXIS S30 Recorder Series. Qualified for up to 1,000 doors with access control only. Tested with:
20 live view clients
2 clients performing heavy playback or scrubbing operations

Hardware

Processor

Intel® Xeon® E processor

Memory

1 x 16 GB

Storage

Cold swappable Enterprise Class SATA HDD, 7200 rpm.
Total HDD slots: 2
Free HDD slot: 1
Out-of-the-box storage: 12 TB (1x 12 TB)

RAID

Factory RAID level: Not configured
Supported RAID levels: 0, 1

Power

450 W Platinum
(100–240 V AC), 6.5–3.5 A, 50/60 Hz

Power consumption

Typical: 55 W (307.1 BTU/h)
Maximum: 70 W (409.5 BTU/h)

Connectors

Front side:

1x USB 2.0
1x iDRAC direct port

Rear side:

1x USB 2.0
1x USB 3.2
1x VGA
1x Serial port
1x iDRAC dedicated Ethernet port
2x RJ45 1 Gbps

Video

Video streaming

Not intended for local viewing of video. Recommended to use Axis workstations.

Approvals

Supply chain

TAA compliant

EMC

EN 55035, EN 55024, EN 55032 Class A,
EN 61000–3–2, EN 61000–3–3
Australia/New Zealand: RCM AS/NZS CISPR 32 Class A
Canada: ICES–3(A)/NMB–3(A)
Japan: VCCI Class A
Korea: KS C 9835, KS C 9832 Class A
USA: FCC Part 15 Subpart B Class A
Taiwan: CNS 15936

Safety

CAN/CSA C22.2 No. 62368–1 ed. 3,
IEC/EN/UL 62368–1 ed. 3, RCM AS/NZS 62368. 1:2018,
IS 13252

Cybersecurity

Edge security

Support for encrypted operating system drive and recording drive
FIPS 140–2 level 2 certified Trusted Platform Module (TPM 2.0)
SBOM
Secure Boot

General

Operating system

Built-in operating system recovery: yes
Operating system drive: 480 GB SSD

Remote server management

iDRAC 9 basic license

Operating conditions

10 °C to 35 °C (50 °F to 95 °F)
Humidity 8–80% RH (non-condensing)

Storage conditions

–40 °C to 65 °C (–40 °F to 149 °F)
Humidity 5–95% RH (non-condensing)

Dimensions

496.74 x 482 x 42.8 mm (19.56 x 19 x 1.68), 1U chassis

Rail sizing:

Type: static, square hole

Minimum rail depth¹: 622 mm (24.49 in)

Product installation depth²: 461.14 mm (18.16 in)

Rail adjustability range³: 608–879 mm (23.94–34.61 in)

For more information, see the Dell EMC Enterprise Systems Rail Sizing and Rack Compatibility Matrix

Weight

8.5 kg (18.7 lb)

Included accessories

Dell Ready Rails 1U Static Rails, C13 to C14 power cord for rack PDU (Wall plug power cords are not included)

Optional accessories

Axis workstations

Enterprise hard drives

For more accessories, see [axis.com](https://www.axis.com)

Services

Next Business Day Onsite Support

Keep Your Hard Drive

Warranty

5-year warranty, see [axis.com/warranty](https://www.axis.com/warranty)

Export control

This product is subject to export control regulations, and you should always comply with all applicable national and international export or re-export control regulations.

Sustainability

Substance control

RoHS in accordance with EU RoHS Directive 2011/65/EU/, as amended by 2015/863/EU.

REACH in accordance with (EC) No 1907/2006. For SCIP UUID, see echa.europa.eu.

Materials

Recycled plastics material content: 65.0% (Post Consumer recycled)⁴

To read more about sustainability at Axis, go to [axis.com/about-axis/sustainability](https://www.axis.com/about-axis/sustainability)

Environmental responsibility

[axis.com/environmental-responsibility](https://www.axis.com/environmental-responsibility)

Axis Communications is a signatory of the UN Global Compact, read more at [unglobalcompact.org](https://www.unglobalcompact.org)

1. Measured from the outside-facing surface of the front rack post until the end of the rail.

2. Measured from the outside-facing surface of the front rack post to the back of the product.

3. The allowable distance between the outside-facing surface of the front and rear rack posts.

4. Measured as a percentage of total amount of plastic (by weight) in the product as per guidance in EPEAT standard as applies to plastics parts

AXIS Camera Station Pro

For details about AXIS Camera Station Pro features and functions, see the AXIS Camera Station Pro datasheet on [axis.com](https://www.axis.com)

Highlighted capabilities

SBOM (Software Bill of Materials)

SBOM is a detailed list of all software components included in an Axis product, including third-party libraries and license information. This list provides customers with insight into the product's software composition, facilitating the management of software security and meeting transparency requirements.

TPM (Trusted Platform Module)

TPM is a security chip integrated into Axis devices to provide a secure environment for storing and processing sensitive data. As a component providing a set of cryptographic features, the TPM protects information from unauthorized access. Specifically, it securely stores the private key, which never leaves the TPM, and processes all related cryptographic operations within the module itself. This ensures the secret part of the certificate remains safe even in the event of a security breach. By enabling features like encryption, authentication, and platform integrity, the TPM contributes to safeguarding the device against unauthorized access and tampering.

Secure Boot

Secure Boot is a security system that ensures only approved software (operating system and embedded switch firmware when applicable) runs on an Axis device at startup. It uses a boot process consisting of an unbroken chain of cryptographically validated software, starting in immutable memory (boot ROM), to verify the authenticity of the software. By establishing the trust chain, Secure Boot guarantees that the device only executes software with a valid digital signature, preventing malicious code from running on the device and ensuring the device boots only with a signed software.

For more information, see [axis.com/glossary](https://www.axis.com/glossary)