Synergy 21 LED floodlight 50W RGB-WW (RGB-CCT) IP65 230V *Milight/Miboxer*



ERG [*]
F

kwh/1000h:	50,00
Lumens:	4000
Watt:	50,0
Nominal Service Life:	35000 Std.
Switching Cycles:	50000
Opt. Ambient Temperature.:	25 °C



Experience powerful and versatile lighting with the **Miboxer floodlight 50W RGB-CCT**. This floodlight not only offers you outstanding light output, but also a wide range of control options and high energy efficiency.

The **Miboxer floodlight** can be controlled with a **radio remote control** and a **WLAN controller** for iOS and Android, both available separately. This allows you to control your lighting conveniently and flexibly and adapt it to your needs. With an output of **50W** for white LEDs and **36W** for RGB LEDs, this spotlight delivers an impressive brightness of **3500-4000 lumens** with a luminous efficacy of **80 LM/W**.

The colour temperature can be flexibly adjusted between **2700-6500K**, which enables perfect lighting for every situation. The wide **beam angle of 160**° ensures generous illumination of large areas, while the high **colour rendering index (CRI >80)** ensures natural and vivid colour rendering. Thanks to the robust **aluminium housing** and the **IP65 protection rating**, the spotlight is ideal for outdoor use as it is weatherproof and durable.

With a voltage of **AC86-265V / 50-60Hz** and a **power factor of 0.9**, the floodlight works efficiently and reliably. The compact size of **220*50*310.5mm** facilitates installation and integration into your lighting system.

Experience versatile and efficient lighting with the **Miboxer floodlight 50W RGB-CCT**. Perfect for illuminating large outdoor and indoor areas, this spotlight provides a powerful and customisable light source.

Miboxer floodlight 50W RGB-CCT with 160° beam angle

Controllable with wireless remote control and/or WLAN controller for iOS and Android, both available separately, open cable end see accessories

Power: 50W



White LED Power: 50W RGB LED Power: 36W Voltage: AC86-265V / 50-60Hz Kelvin: 2700-6500K Luminous Flux: 3500-4000LM Luminous Efficiency: 80LM/W CRI: >80 Beam Angle: 160° PF: =0.9 Material: Aluminium Material IP Rate: IP65 Size: 220*50*310.5mm

Energy efficiency class: F kWh/1000h: 50


Attributes

Attribute	Value
Abstrahlwinkel:	160
Dimmbar:	Ja
Grösse:	220*50*310,5
LED - Gehäusematerial:	Aluminium
Lichtfarbe:	RGB-WW
Lichtfarbe in Kelvin:	2700~6500
Lumen:	3500-4000
Schutzklasse:	IP65
Volt:	230
Weight:	1.9 Kg
Warranty:	24.00 Months


Additional Images

www.synergy21.de

Part No.: 148113 Vendor Part No.: FUTT02












High lumen LED Chips





www.synergy21.de





COMPATIBLE REMOTE SHEET ***** 0.9 (1000) (1000) • • • • **~~??** 8 in in E3

Accessories

Part No.	Name
147981	Synergy 21 LED remote RGB-WW (RGB-CCT) 8 zones *Milight/Miboxer*
147982	Synergy 21 LED remote RGB-WW (RGB-CCT) 4 zones *Milight/Miboxer*
148005	Synergy 21 LED remote smart panel RGB-WW (RGB-CCT) 4 zones *Milight/Miboxer*
148006	Synergy 21 LED remote smart panel RGB-WW (RGB-CCT) 8 zones *Milight/Miboxer*
181054	Synergy 21 LED remote WLAN controller *Milight/Miboxer*
148507	Synergy 21 LED remote WLAN controller smart light *Milight/Miboxer*

www.synergy21.de

Part No.	Name
148726	Synergy 21 - Waterproof connector 1:1
148727	Synergy 21 - Waterproof connector 1:2
148730	Synergy 21 - Waterproof connector box 3 ports
148729	Synergy 21 - Waterproof connector box 3 ports transparent
148728	Synergy 21 - Waterproof connector box 4 ports
147265	Netzkabel 230V Schutzkontakt CEE7(Stecker)->Open End mit Adernendhülsen, 1,8m,Black

www.synergy21.de