

| EFB NO. | COLOR |
|---------|---------|
| K5510.X | GREY |
| K5511.X | YELLOW |
| K5512.X | RED |
| K5513.X | BLUE |
| K5514.X | GREEN |
| K5515.X | BLACK |
| K5516.X | ORANGE |
| K5518.X | WHITE |
| K5519.X | MAGENTA |


| ALL LENGTH (L) | |
|----------------|-------------|
| 500mm±5 | 7500mm±75 |
| 1000mm±10 | 10000mm±100 |
| 1500mm±15 | 15000mm±150 |
| 2000mm±20 | 20000mm±200 |
| 3000mm±30 | 25000mm±250 |
| 5000mm±50 | 30000mm±300 |

ROHS COMPLIANT


| Impedance | Nom.100 Ohm±20% | | | | | | | | | | | | |
|-------------|-----------------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Frequency | MHZ | 1 | 4 | 8 | 10 | 16 | 20 | 25 | 31.25 | 62.5 | 100 | 200 | 250 |
| NEXT | DB | 65 | 63.04 | 58.16 | 56.58 | 53.23 | 51.63 | 50.03 | 48.42 | 43.38 | 39.93 | 34.78 | 33.09 |
| Attenuation | DB/100m | 2.15 | 4.02 | 5.66 | 6.33 | 8.04 | 9.02 | 10.12 | 11.38 | 16.45 | 21.26 | 31.47 | 43.67 |
| Returnloss | DB | 19 | 19 | 19 | 19 | 17.98 | 17.49 | 17.01 | 16.53 | 14.02 | 12 | 8.98 | 7.99 |

| | | | |
|-----|-----------|---|-------|
| c | CABLE | SSTP CAT.6 27AWG stranded 4pairs cable LSZH OD=6.2mm Printing : CAT.6 SSTP 4X2XAWG27/7 PIMF ISO/IEC 11801 & EN50173 TIA/EIA 568B.2-1 HALOGEN FREE ***GIGABIT*** | L mm |
| b | OVERMOLD | PVC 75A / LENGTH IMPRINT ON BOOT | 8 g |
| a | CONNECTOR | RJ45 8P8C'S SHIELDED GOLD PLATED 3-50u" | 2 Pcs |
| NO. | MAT.NAME | DESCRIPTION | Q'TY |

| | | | |
|----------|-----------------------|----------|------------|
| ITEM | K55XX.X | | |
| DRAWING | SSTP 27AWG PATCH CORD | | |
| UNIT | mm | SCALE | REV |
| DRAWN BY | CHECK BY | APPRO BY | DATE |
| | | | 2006.11.26 |



Rawcable Specification K55xx

| (Product name) | | CAT.6 S/STP | | |
|---|-----------------|--|-----------------------------|---|
| (items) | | (unit) | (The specification value) | |
| (AWG size) | | Awg | #27 | |
| (core number) | | Pcs | 4P | |
| c r o s s e d w i r e | (conductor) | (material) | tinned copper wire | |
| | | (filling) | | |
| | | (structure) | No.mm | |
| | | (crossed O.D) | mm | 0,4 |
| | (insulate) | (material) | | HDPE |
| | | (thickness) | mm | 0,335 |
| | | (O.D) | mm | 1,05 |
| | | (color) | | white-blue white-yellow pink-green white-brown |
| | (tapes) | (material) | | AL flake |
| | | (structure) | | |
| | | (overlap rate) | % | 25 |
| | (earthing wire) | | (material) | |
| (braid) | | (structure) | No.mm | |
| (jacket) | | (material) | tinned copper wire 16*5*0.1 | |
| (print) | | (shield rate) | % | |
| (structure drawing) | | (material) | 65 | |
| (establishment) | | (minimum thickness) | mm | |
| (date) | | (standard thickness) | mm | |
| (print) | | (O.D) | mm | |
| (structure drawing) | | (color) | PVC<LSOH> | |
| (establishment) | | CAT 6 SSTP 4x2xAWG27// PIMF IS O/IEC 11801 & EN 50173 TIA/EIA 568B 2-1 HALOGEN FREE ***GIGABIT*** | | |
| (date) | | <div style="display: flex; align-items: center;">  <div style="margin-left: 20px;"> <p>wire</p> <p>AL flake</p> <p>braid</p> <p>jacket</p> </div> <div style="margin-left: 20px;"> <p>1--white</p> <p>2--blue</p> <p>3--white</p> <p>4--yellow</p> <p>5--pink</p> <p>6--green</p> <p>7--white</p> <p>8--brown</p> </div> </div> | | |

(establishment)

(date)