

ALLNET ALL5003CPU / CPU Board Ralink RT5350

>>> [Go to the shop article](#)



EAN CODE



With the new CPU module ALL5003 you are able to implement a variety of solutions that require network access (via Ethernet or WLAN):

- Machine control
- Building automation
- Autonomous measuring devices
- Safety Engineering
- Robotics
- Conveyors
- Lighting control
- and much more

Eight usable GPIOs, and the 360 MHZ-MIPS-CPU-Core with 32 MB RAM and 32 MB ash range for more challenging tasks.

- CPU: Ralink 3350, 360 MHz (MIPS)
- Flash: 32 MB
- RAM: 32 MB
- 8x usable GPIO pins
- 1x SPI
- 1x JTAG
- 1x I2C
- 1x USB-Host-Port
- 1x serial port (console)
- 2x U.FL socket
- 1x LAN-Port 10/100 Mbit



Part No.: 92763
Vendor Part No.: ALL5003CPU

Further technical data:

- Dimensions: 65 x 21 mm
- Mounting: any
- Pin connector pin spacing 1.27 mm single-breasted
- 2x 20 Pins

Depending on whether one uses straight or angled socket board, you can equip the modules horizontally or vertically.

All of the important signals are on the rst socket board (pin 1 to 20), thus it is possible to operate the module with this one socket board.