



**AC WLAN UAE/USB PoE Up rw  
22610409**

Up-WLAN-Accesspoint, with center plate and wall plate, 150 Mbit/s, 802.11 b/g/n, WEP/WPA2, operating mode as well as bridge, repeater, with timer- and time switching function, indication of functions at RJ45 - outlet, reset with reset magnet, integrated d  
EAN: 4043921663158  
pure white (similar RAL 9010)

**Produktbeschreibung**

**Performance features**

|                                                       |                                                       |
|-------------------------------------------------------|-------------------------------------------------------|
| Wireless data rate                                    | 150 Mbit/s                                            |
| Wireless data standart                                | IEEE 802.11 b/g/n                                     |
| Wireless data standart                                |                                                       |
| Band                                                  | 2,4 GHz                                               |
| Security and encryption                               | WEP, WPA, WPA2                                        |
| Types of function                                     | Accesspoint, Repeater, Client (WDS), Client (Relayed) |
| Settings in integrated Web server                     | •                                                     |
| Additional data output via RJ45 jack (100 Mbit/s)     | •                                                     |
| Additional USB port (USB2.0)                          | •                                                     |
| USB for either network devices / printserver / Router | •                                                     |
| Integrated WLAN antenna                               | •                                                     |
| Timer functions LAN / WLAN                            | •                                                     |
| Operating display for LAN/WLAN via LED                | •                                                     |
| Repeater function                                     | •                                                     |
| Guest access                                          | •                                                     |
| Reset via reset magnet                                | •                                                     |
| fits in commercial flush-mount installation boxes     | •                                                     |
| LAN - screw terminals                                 | •                                                     |
| Design compatible (TAE)                               | •                                                     |

**Mechanical characteristics**

|        |       |
|--------|-------|
| Weight | 112 g |
|--------|-------|

**Dimensions**

|       |       |
|-------|-------|
| Width | 80 mm |
|-------|-------|

|        |       |
|--------|-------|
| Height | 80 mm |
|--------|-------|

|       |       |
|-------|-------|
| Depth | 50 mm |
|-------|-------|

**Electrical characteristics**

|                         |                   |
|-------------------------|-------------------|
| Rated operating voltage | 48 V, PoE Class 0 |
|-------------------------|-------------------|

|             |           |
|-------------|-----------|
| Power drain | max. 3 VA |
|-------------|-----------|

|                   |                                  |
|-------------------|----------------------------------|
| Power requirement | PoE via data input (PoE Class 0) |
|-------------------|----------------------------------|

|           |                             |
|-----------|-----------------------------|
| PoE input | Class 2 (6,49 W) RJ 45 port |
|-----------|-----------------------------|