

**Mechanical characteristics**  
cables

interface dimension acc. to assembly code  
 inner conductor  
 outer conductor  
 mating life  
 coupling torque

**Components**

centre contact  
 outer contact  
 other metal parts  
 crimp ferrule  
 insulator  
 gasket

**Electrical characteristics**

impedance  
 frequency  
 return loss  
 insertion loss  
 working voltage  
 voltage proof  
 insulation resistance  
 contact resistance centre contact  
 contact resistance outer contact

**Environment**

operating temp.  
 RoHS compliant

**Mechanische Eigenschaften**  
Kabel

Steckgesicht nach ...  
 Montageanleitung  
 Innenleiter  
 Außenleiter  
 Steckzyklen  
 Kupplungsdrehmoment

**Bauteile**

Innenkontakt  
 Außenkontakt  
 sonstige Metallteile  
 Crimprohr  
 Isolierung  
 Dichtung

**Elektrische Eigenschaften**

Wellenwiderstand  
 Frequenz  
 Rückflusdämpfung  
 Einfügedämpfung  
 Betriebsspannung  
 Prüfspannung  
 Isolationswiderstand  
 Durchgangswiderstand Innenleiter  
 Durchgangswiderstand Außenleiter

**Umgebung**

Betriebstemperatur  
 RoHS konform

G58 :  
 ECOFLEX 10 SSB Elektronik; Hyperflex 10/.400"  
 M&P; RF 400 UF Siva; Ultraflex 10/.400" M&P  
 IEC 61169-16

B3426  
 crimp  
 crimp  
 >500  
 4 - 6 Nm

**materials / Material**



brass / Messing  
 brass / Messing  
 brass / Messing  
 copper / Kupfer  
 PTFE  
 silicone/ Silikon

**Finish /Oberfl.**

Cu2Ag5  
 CuSnZn3  
 CuSnZn3  
 CuSnZn3

50 Ω  
 0-11 GHz  
 (a) typ.: 1 GHz-32dB; 2 GHz-29dB; 6 GHz-21 dB  
 < 0.1 dB  
 < 1 kVeff / 50 Hz  
 1.5 kVeff / 50 Hz  
 > 5 GΩ  
 < 2 mΩ  
 < 0.5 mΩ

-30°C / 100°C  
 2011/65/EU

Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	gez./ drawn	Datum/ date	Name/ name	Gewicht/ weight [g]
					19.05.2020	JA	
				gepr./ appr.	20.05.2020	BJ	ca./approx. 33
			Maßstab/ scale	Benennung/ title			
			2:1	N Straight Plug N-Kabelstecker			
			untol. Maße/ dim. without tolerances according to	Untert./ doc. type	Zeichnungsnr./ drawing no.		 Maße/ dimensions: mm
			K	J01020A0184			
a	31536	01.09.2020	MA	Ersatz für/ replaces	EWB90042-10		Original : DIN A4 Blatt/ sheet 1 von/ of 1