

## **Novo**Touch




## **NovoTouch OPS Module VKW30**

Full-featured detachable PC module designed exclusively for the NovoTouch collaborative and interactive flat panel displays

## FEATURES

- Full-featured detachable PC module for seamless integration into the NovoTouch interactive flat panel display
- Powerful 8th generation Intel<sup>®</sup> Core<sup>™</sup> processor with integrated Intel<sup>®</sup> UHD graphics chipset
- Supports fast SSD and DDR4 RAM in a variety of configurations (Varies by model)
- HDMI-Out (4K@30Hz) for connection to secondary display
- Up to five (5) high speed USB ports (USB-v2 (x2) (USB-v3 (x2) (USB 3.1 Type C (x1) for connectivity to a variety of devices including but not limited keyboards, mice and flash drives
- Integrated RJ45 port for network monitoring and management solutions
- Reduces clutter & promotes a cable-free workplace
- Easy installation and maintenance
- Rugged steel chassis for extra strength and integrity
- Kensington<sup>®</sup> security slot for prevention against theft or unapproved removal







## **Novo**Touch

Model Number			VKW30-i5	VKW30-i7
Product Compatibility			EK653i, EK753i, EK863i	
Туре			Detachable PC Module	
Operating System			Windows 10 Recommend (Not Included)	
Interface			80PIN Connector	
	CPU (Intel® 8 Generation CPU)		Intel® Core™ i5-8265U 1.6GHz	Intel® Core™ i7-8565U 1.8GHz
Hardware	RAM		DDR4 8GB	DDR4 8GB
	Storage (M2. SSD)		256GB	256GB
	Graphics (Integrated)		Intel <sup>®</sup> UHD Graphics 620	
	Sound Card		Integrated High Definition Audio Stereo	
	Networking		Integrated 10/100/1000Mbps Adaption	
Connectivity	Input Audio		Microphone-In (3.5mm)	
	Output	Display	HDMI-Out v1.4 (4K@30Hz)	
		Audio	Audio-Out (3.5mm)	
	Ethernet		RJ45	
	USB		USB 2.0 (x2), USB 3.0 (x2), USB 3.1 Type C (Gen 2)(Data Only)	
	Wireless		802.11ac (2.4GHz/5GHz)	
	Bluetooth		V4.2	V4.2
LED Indicator		HDD LED, Power LED		
Buttons		Power Button, System Recovery Button		
	Operating Temperature		0°C - 45°C (32°F - 113°F)	
Environmental Conditions	Operating Humidity		10% - 90% RH	
	Storage Temperature		-20°C - 60°C (-4°F - 140°F)	
	Storage Humidity		10% - 90% RH	
Power	Power Supply		Internal Power Supply Module	
	Power Requirements		12 - 19V, DC 5.0A	
	Max Power		60W	
	Standby Power		1.2W	
Accessories		Antennas (x2), Documentation Kit		
Security		Kensington® Security Slot, TPM2.0		
Available Color		Black		
Weight		0.74kg (1.6lbs)		
Dimensions (L x W x H)		202 x 133.5 x 30mm (7.9 x 5.3' x 1.2')		

©2021 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subjection to change without prior notice.

