

ALLNET ALL126AM3 / VDSL2 Master CO over 2 Wire



EAN CODE



VDSL2 Master Modem for leased lines via 2-wire connections up to a length of max. 2200 meters and a bandwidth of 100 Mbit/s (depending on length)

Highlights:

- VDSL CO master modem according to VDSL2 standard for high data throughput
- Integrated 4-port Ethernet 10/100Mbps switch
- Two RJ11 sockets for telephone/line connection
- Integrated DSL splitter and overvoltage protection
- Various VDSL bandwidth profiles configurable
- Configuration via web browser (HTTP/HTTPS)
- Energy-saving, low power consumption (only approx. 5.5W)
- VDSL technology from metanoia to 100Mbps/symm.
- Can be used for pure point-to-point connection in connection with a slave CPE modem e.g. ALL126AS3
- Network connection via twisted two-wire telephone cable
- Parallel telephony connection for analogue telephone on the same line possible

The ALLNET ALL126AM3 VDSL Master Modem can be used in conjunction with the ALL126AS2 VDSL Slave Modem to create leased lines over a simple 2-wire copper line with a length of up to 2.5 kilometers.

Bandwidths of up to 100 Mbps are possible at short distances.



No. d'article: 149851
Numéro de fabricant: ALL126AM3

At the same time, analog telephones can be connected and operated via the same line. Existing telephone cabling can thus also be used for high-performance data services. Especially for outbuildings / hotels / hospitals, this technology is the optimal solution to provide cost-effective, high-performance network applications via 2 twisted-pair cables with minimum effort.

Technical Details:

Element	Spezifikation
Chipsets:	Metanoia VDSL MT-5311 ARM Cortex A9
Standards:	IEEE802.3 standard IEEE802.3u standard
Physical Interface:	ITU-T G993.2 VDSL2 standard Complies with ITU-T G993.2 Connector: RJ-11 On board POTS/ISDN splitter On board surge protection
Max. Bandwidth:	Symetric 100 Mbps max. 300m
LED-Indicators:	LAN: Act/Link, Power; VDSL2: Link
IP Adress QoS:	- IPv4/IPv6 - 8 queue - MFC / DSCP
Features:	- 802.1P VLAN priority - Adopts ARM Cortex A9 dual-core processor - support http/ https web management - Support CO side bridge mode - Support 8 bands selectable - Support USB 2.0 for Dongle device - Support G.998.4 G.INP - On board surge protection for Line port - Support 8 queue MFC/ DSCP both type - Support SSL/ SSH Security - Support IPV4/ IPV6 address - Support configuration backup and restore - Support Dual Firmware Image Backup - Support TR-069 - VLAN Tag pass through - Mac Address based filtering
Power-Consumption:	5.52W
Temperature:	Temperature Operating: 0°C ~ 50°C (32°F ~ 122°F) Temperature Storage: -20°C ~ 70°C (-4°F ~ 150°F)
Humidity:	10 to 90% (non-condensing)
Dimensions:	184 x 146 x 40 mm (7.2" x 5.74" x 1.57")



No. d'article: 149851
Numéro de fabricant: ALL126AM3

Marks:
Package Content:

CE
- ALL126AM3 VDSL Master Modem
- 12V 1A Powersupply
- 1 Patchcable LAN
- 1 RJ11 Telefon cable

Images supplémentaires



Accessoires

No. d'article	Désignation
99305	ALLNET TP Cat 6 Überspannungs-/Blitzschutz Surge Protector ALL95100 Indoor
103889	ALLNET Punkt-zu-Punkt Modem VDSL via 2-Draht managed Slave "ALL126AS3"
102395	ALLNET Punkt-zu-Punkt Modem VDSL via 2-Draht unmanaged "ALL-MC115VDSL2"
144404	ALLNET ISP Bridge Modem VDSL2 / ADSL mit Vectoring "ALL-BM200VDSL2V"
105571	ALLNET Ersatznetzteil 12V/2,0A