



# **ALLNET**

## **ALL-CAM2372-WP**

### **2MP 2X Network PTZ Mini Dome Camera**

- *1 / 3" Progressive Scan CMOS*
- *2,2 Megapixel*
- *2fach optischen Zoom, 16x digitalen Zoom*
- *Smart-Tracking, ROI-Codierung*
- *bis zu 128 GB SD-Kartenspeicher*
- *integriertes Mikrofon*
- *1920x1080 Full HD Auflösung bei 30fps*
- *3D intelligente Positionierfunktion*
- *High-PoE / PoE Stromversorgung*
- *Wifi*

**Article: 123585**



<b>Technical data:</b>	
<b>Camera</b>	
Image Sensor	1/3" Progressive Scan CMOS
Min. Illumination	F2.0, AGC On : Color : 0.05 lux, B/W : 0.01 lux
Max. Image Resolution	1920(H) × 1080(V)
Focal Length	3.6~8.6mm, 2x
Digital Zoom	16X
Zoom Speed	Approx.1s(Wide~Tele)
Angle of View	80-64.5 degree (Wide~Tele)
Aperture Range	F2.0
Focus Mode	Auto / Semiautomatic / Manual
DWDR	Support
S / N Ratio	≥ 52dB
Shutter Time	1/1 ~ 1/10,000s
AGC	Auto / Manual
White Balance	Auto / Manual / ATW/Indoor/Outdoor/Daylight lamp/Sodium lamp
Day & Night	IR Cut Filter
Privacy Mask	8 privacy masks programmable
Enhancement	3D DNR, HLC/BLC
<b>Pan and tilt</b>	
Range	Pan: 0~350°; Tilt: 0°~90°
Speed	Pan Manual Speed: 0.1°~100°/s, Pan Preset Speed: 100°/s Tilt Manual Speed: 0.1°~80°/s, Tilt Preset Speed: 80°/s
Number of Preset	300
Park Action	Preset
Scheduled Task	Preset / Reboot / Self test / Aux output
<b>Alarm</b>	
Alarm I/O	1/1
Alarm Trigger	Intrusion detection, Line crossing detection, Motion detection, Audio Exception Detection, Dynamic analysis, Tampering alarm, Network disconnect, IP address conflict, Storage exception
Alarm Action	Preset, Recording, Relay output, Upload center, Upload FTP, Email linkage
<b>Wi-Fi Specification</b>	
Wireless Standards	IEEE802.11b, 802.11g, 802.11n
Frequency Range	2.4 GHz ~ 2.4835 GHz
Channel Bandwidth	20/40MHz Support



<b>Input/output</b>	
Audio Input	1 built-in microphone; 1 audio input (Mic/Line in), 2~2.4V[p-p]; output impedance: 1K $\Omega$ , $\pm$ 10%
Audio Output	1 output, Line level, impedance: 600 $\Omega$
<b>Network</b>	
Ethernet	10Base-T / 100Base-TX, RJ45 connector
Main Stream	50Hz: 25 fps (1920 $\times$ 1080); 60Hz: 30 fps (1920 $\times$ 1080)
Sub Stream	50Hz:25fps(704 $\times$ 576), 25fps(352 $\times$ 288), 25fps(320 $\times$ 240) 60Hz:30fps(704 $\times$ 480), 30fps(352 $\times$ 240), 30fps(320 $\times$ 240)
Image Compression	H.264/ MJPEG
Audio Compression	G.711/G.722/G.726/MP2L2
Protocols	IPv4/IPv6, HTTP, HTTPS, 802.1X, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTP, TCP, UDP,IGMP, ICMP, DHCP, PPPoE
Simultaneous Live View	Up to 20 users
Mini SD Memory Card	Support up to 64GB Micro SD/SDHC/SDXC card. Support Edge recording
User/Host Level	Up to 32 users,3 Levels: Administrator, Operator and User
Security Measures	User authentication (ID and PW); Host authentication (MAC address); IP address filtering
<b>Integration</b>	
Application programming	Open-ended API, support Onvif, PSIA, CGI and Genetec
Web Browser	IE 7+, Chrome 18 +, Firefox 5.0 +, Safari 5.02 +
Power	POE&12 VDC, Max. 5.5W
Working Temperature	-10 ~50 (14 ~122 )(indoor dome)
Humidity	90% or less
Protection Level	IP54, TVS 4,000V lightning protection, surge protection and voltage transient protection
Certification	FCC, CE, UL, RoHS, IEC/EN 61000, IEC/EN 55022, IEC/EN 55024, IEC /EN60950-1
Dimensions	120 $\times$ 83.7mm
Weight (approx.)	600g
Mount Option	Wall mount